

# To the Point 4732

Ebony 1415

## Specifications

---

### Contents

56% polyester  
44% post-consumer recycled polyester

### Weight

12.4 ± 1.0 oz./lin. yd.

### Width

54" min. useable

### Repeat

horizontal 0.125"  
vertical 0.15"

### Treatment

BLOCKaide® stain repellent

### Backing

SBR backcoating

### Treatment

BLOCKaide® stain repellent

### Backing

SBR backcoating

## Cleaning Code

---

<p>Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.</p>

## Performance

---



### Breaking Strength (ASTM D5034)

295 lbf min. warp and 330 lbf min. fill

### Tear (ASTM D2261)

30 lbf min. warp and 35 lbf min. fill

### Seam Slippage (ASTM D4034)

110 lbf min. warp and 85 lbf min. fill

### Pilling resistance (ASTM D3511)

Class 4

### Colorfastness to light (AATCC 16.3 Option 3)

Grade 4 min. at 40 hours

### Colorfastness to crocking (AATCC 8)

Grade 4 min. dry & Grade 3 min. wet

### Wyzenbeek Abrasion resistance (ASTM D4157)

100,000 double rubs min. cotton duck

### Flammability

CA Technical Bulletin 117-2013 Section 1

## Miscellaneous

---

Proudly woven in North America supporting our local communities. Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.



