

# Revival 9217

Navy 5010

## Specifications

---

### Contents

55% nylon  
29% pre-consumer recycled polyester  
13% polyester  
3% olefin

### Weight

17.0 ± 1.0 oz./lin. yd.

### Width

54" min. useable

### Repeat

6.75" vertical and horizontal

### Treatment

BLOCKaide® stain repellent

### Backing

acrylic backcoating

### Treatment

BLOCKaide® stain repellent

### Backing

acrylic backcoating

## Cleaning Code

---

<p>Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.</p>

## Performance

---



### Breaking Strength (ASTM D5034)

150 lbf min. warp and 200 lbf min. fill

### Tear (ASTM D2261)

10 lbf min. warp and 20 lbf min. fill

### Seam Slippage (ASTM D4034)

50 lbf min. warp and fill

### Pilling resistance (ASTM D3511)

Class 4 min.

### Colorfastness to light (AATCC 16.3 Option 3)

Grade 4 min. at 40 hours

### Colorfastness to crocking (AATCC 8)

Grade 4 min. dry & Grade 3 min. wet

### Wyzenbeek Abrasion resistance (ASTM D4157)

60,000 double rubs min.

### Flammability

CA Technical Bulletin 117-2013 Section 1

## Miscellaneous

---

Every effort has been made to ensure color accuracy of the digital images, however, please order a sample before specification. Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Proudly woven in North America supporting our local communities.



